



## INTO POD 4

POD 4 is perfect for private or confidential meetings and adaptable workspaces. Its insulating structure offers excellent acoustic protection from disruptive sounds. PODs can be installed without changes to existing structures or walls, as well as reassembled in another location.

## TECHNICAL DETAILS

### Material description

- MDF frame with water based paint
- Painted MDF door and door panels
- Door handle with satin finished stainless steel
- Laminated acoustic safety glass windows 10 mm
- Acoustic panel on the ceiling
- Back wall and floor coated with carpet
- Window and ceiling lights with wall switch
- Own ventilation with speed mode

### Additional info

- POD sound insulation value  $R_w$  36 dB
- Door and POD handedness left or right
- Three electrical sockets or two electrical sockets + data outlet included
- Electrical socket position on the left, right or back wall
- Electricity connection from the ceiling or floor
- Glass wall includes the INTO stripe window taping
- POD outside and inside colour white, light grey or dark grey as a standard
- Standard carpet category 1: Desso Flux, category 2: Desso Palatino\*

### Options

- LED lighting on acoustic panels instead of ceiling light
- Door and door panels with American oak
- Door lock
- INTO DISPLAY BOX or CABINET -screen wall
- Furnished with pre-selected furniture combinations
- Tailored window taping in the glass wall
- Readiness for connection to building's own ventilation and sprinkling systems

### Measurements

W3400 x D2500 x H2320 mm

### Delivery

- Assembled on site
- Assembly by Certified Installer or under supervision

\*For more information, see INTO Standard Materials -file

### CONTACT

www.intoconcept.com  
contact@intoconcept.com