

POD 1

POD 1 is the number one choice for private phone calls and a workspace for tasks which demand focusing. Its insulating structure offers excellent acoustic protection from disruptive sounds. The PODs can be installed without changes to existing structures or walls, as well as reassembled in another location.

TECHNICAL INFORMATION

Three electrical sockets + data outlet included.
Electricity connection from the ceiling or floor.
The length of the electric cord is 3 m.
Glass window includes the INTO stripe window taping.
Automated electric sockets, ventilation with speed mode, lights with electronic motion sensor and separate electronic control unit on the wall.
Installation wheels included.

MATERIAL DESCRIPTION

Melamine or veneered frame.
Painted MDF door and door side panels.
Door handle with satin finished stainless steel.
Laminated acoustic safety glass window 10 mm.
Acoustic panel on the ceiling.
Floor and back wall coated with carpet.


POD surface options:	White NCS S 0500-N Dark grey NCS S 7500-N Pine American Oak Black Oak
POD inside color:	White NCS S 0500-N
Carpet options:	Fletco Ex-dono quartet
Ceiling acoustic panel:	GABRIEL - Soul
Door color options:	White smooth NCS S 0500-N American Oak Clear glass 10 mm

MEASUREMENTS


W1700 x D1700 x H2220 mm
Door 9 x 21

Inner dimensions
W1500 x D1300 x H2040 mm

POD 1 LEFT




POD 1 RIGHT



SURFACE FINISHES FOR POD ROOMS

STANDARD PRICE, CATEGORY 1

Melamine color options



NCS S 0500-N




NCS S 7500-N

PRICE CATEGORY 2

Veneer material options



Pine



American oak



Black oak


SURFACE FINISHES FOR DOOR & DOOR SIDE PANELS

STANDARD PRICE, CATEGORY 1



NCS S 0500-N

PRICE CATEGORY 2



American oak



Clear glass 10 mm

comes with white door panels

CARPETS FOR POD ROOMS: EX-DONO QUARTET FROM FLETCO | STANDARD PRICE, CATEGORY 1

Composition: Polyester non woven

Static electrical propensity: Antistatic

Impact sound reduction: 25 dB

Classification for use: Commercial / heavy use

Fire resistant: Yes



393300




393340



393350

Ask for more colors: sales@intoconcept.com



CEILING ACOUSTIC PANEL FABRIC: SOUL FROM GABRIEL | STANDARD PRICE, CATEGORY 1

Composition: 100% wool

Lightfastness: 5-7

Rubbing fastness: 4/wet, 4-5/dry

Sustainability: Complies with STANDARD 100 by OEKO-TEX

Meet Möbelfakta requirements

Cleaning: regular vacuum cleaning

Fire resistant: Yes (S 476 Part 7, class 1 ÖNORM B 3825-B1-3800-Q1 UK)




66104



67039



68131




64086



62059



61196



60182

