

POD 2

The POD 2 small meeting room is ideal for spontaneous but confidential meetings and as an adaptable workspace. Its insulating structure offers excellent acoustic protection from disruptive sounds.

TECHNICAL INFORMATION

Three electrical sockets + data outlet included.
 POD electricity connection from the ceiling or floor.
 The length of the electric cord is 3 m.
 Automated electric ventilation with speed mode, lights with electronic motion sensor, and separate electronic control unit on the wall.
 Glass window includes the INTO stripe window taping.
 Installation wheels included.

MATERIAL DESCRIPTION

Melamine or veneered frame.
 Painted MDF door and door side panels.
 Door handle with satin finished stainless steel.
 Laminated acoustic safety glass windows 10 mm.
 Acoustic panel on the ceiling.
 Floor and back wall coated with carpet.

POD surface options:	White NCS S 0500-N Dark grey NCS S 7500-N Pine American Oak Black Oak
POD inside color:	White NCS S 0500-N
Carpet options:	Fletco Ex-dono quartet
Ceiling acoustic panel:	GABRIEL - Soul
Door color options:	White smooth NCS S 0500-N American Oak Clear glass 10 mm


MEASUREMENTS

W2500 x D1700 x H2220 mm
 Door 9 x 21

Inner dimensions
 W2300 x D1300 x H2040 mm

POD 2 LEFT


POD 2 RIGHT



SURFACE FINISHES FOR POD ROOMS

STANDARD PRICE, CATEGORY 1

Melamine color options




NCS S 0500-N




NCS S 7500-N

PRICE CATEGORY 2

Veneer material options



Pine




American oak



Black oak


SURFACE FINISHES FOR DOOR & DOOR SIDE PANELS

STANDARD PRICE, CATEGORY 1



NCS S 0500-N

PRICE CATEGORY 2



American oak




Clear glass 10 mm

comes with white door panels

CARPETS FOR POD ROOMS: EX-DONO QUARTET FROM FLETCO | STANDARD PRICE, CATEGORY 1

Composition: Polyester non woven
 Static electrical propensity: Antistatic
 Impact sound reduction: 25 dB
 Classification for use: Commercial / heavy use
 Fire resistant: Yes





393300

393340


393350

Ask for more colors: sales@intoconcept.com



CEILING ACOUSTIC PANEL FABRIC: SOUL FROM GABRIEL | STANDARD PRICE, CATEGORY 1

Composition: 100% wool
 Lightfastness: 5-7
 Rubbing fastness: 4/wet, 4-5/dry
 Sustainability: Complies with STANDARD 100 by OEKO-TEX
 Meet Möbelfakta requirements
 Cleaning: regular vacuum cleaning
 Fire resistant: Yes (S 476 Part 7, class 1 ÖNORM B 3825-B1-3800-Q1 UK)



66104

67039

68131

64086

62059

61196

60182

