

POD 4

POD 4 meeting rooms are perfect for private or confidential meetings as well as adaptable work spaces. The acoustic protection in this meeting room is excellent due to its insulating structure. POD 4 meeting rooms can be installed without changes to walls or other existing structures, as well as reassembled in another location.

TECHNICAL INFORMATION

Four electrical sockets + data outlet included
 POD electricity connection from the ceiling or floor.
 The length of the electric cord is 3 m.
 Automated electric ventilation with speed mode, lights with electronic motion sensor, and separate electronic control unit on the wall.
 Glass window includes the INTO stripe window taping.
 Installation wheels included.

MATERIAL DESCRIPTION

Melamine or veneered frame.
 Painted MDF door and door side panels.
 Door handle with satin finished stainless steel.
 Laminated acoustic safety glass windows 10 mm.
 Acoustic panel on the ceiling.
 Back wall and floor coated with carpet.

- POD surface options:
 - White NCS S 0500-N
 - Dark grey NCS S 7500-N
 - Pine
 - American Oak
 - Black Oak
- POD inside color:
 - White NCS S 0500-N
- Carpet options:
 - Fletco Ex-dono quartet
- Ceiling acoustic panel:
 - GABRIEL - Soul
- Door color options:
 - White smooth NCS S 0500-N
 - American Oak
 - Clear glass 10 mm



MEASUREMENTS

W3400 x D2500 x H2220 mm
 Door 9 x 21

Inner dimensions
 W3200 x D2100 x H2040 mm

POD 4 LEFT


POD 4 RIGHT



SURFACE FINISHES FOR POD ROOMS

STANDARD PRICE, CATEGORY 1

Melamine color options



NCS S 0500-N




NCS S 7500-N

PRICE CATEGORY 2

Veneer material options



Pine



American oak



Black oak


SURFACE FINISHES FOR DOOR & DOOR SIDE PANELS

STANDARD PRICE, CATEGORY 1



NCS S 0500-N

PRICE CATEGORY 2



American oak



Clear glass 10 mm

comes with white door panels

CARPETS FOR POD ROOMS: EX-DONO QUARTET FROM FLETCO | STANDARD PRICE, CATEGORY 1

Composition: Polyester non woven
 Static electrical propensity: Antistatic
 Impact sound reduction: 25 dB
 Classification for use: Commercial / heavy use
 Fire resistant: Yes



393300




393340




393350

Ask for more colors: sales@intoconcept.com



CEILING ACOUSTIC PANEL FABRIC: SOUL FROM GABRIEL | STANDARD PRICE, CATEGORY 1

Composition: 100% wool
 Lightfastness: 5-7
 Rubbing fastness: 4/wet, 4-5/dry
 Sustainability: Complies with STANDARD 100 by OEKO-TEX
 Meet Möbelfakta requirements
 Cleaning: regular vacuum cleaning
 Fire resistant: Yes (S 476 Part 7, class 1 ÖNORM B 3825-B1-3800-Q1 UK)



66104



67039



68131




64086



62059



61196



60182

