INTO
the Nordic Silence



POD PHONE SMALL


POD PHONE SMALL is a telephone booth that improves privacy when taking phone calls in open spaces and office environments.

TECHNICAL INFORMATION

AIR FLOW	Fully automated ventilation controlled by motion sensor. As standard, set to 1 hour and is adjustable up to 99 minutes. Air flow 22l/s.
LIGHTS	Fully automated lights controlled by motion sensor. As standard, set to 1 hour and is adjustable up to 99 minutes. LED light set on the ceiling. Lumen 871.
WHEELS	Installation wheels included.
ENERGY CONSUMPTION PER HOUR	Total 0,01895 kWh. Fans 0,00445 kWh. Lights 0,0145 kWh. Max load 8 A.
SOCKET	One power socket on the table.
POWER CONNECTION	From the ceiling or floor. The length of the power cord is 3 m.

MEASUREMENTS

EXTERNAL DIMENSIONS	W1000 x D1200 x H2220 mm
INNER DIMENSIONS	W800 x D800 x H2040 mm
DOOR	8 x 21
PACKAGE DIMENSIONS	W800 x D2400 x H1500 mm
WEIGHT	400 kg 333 kg/m2



INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.

INTO
the Nordic Silence

MATERIAL DESCRIPTION

EXTERIOR	Melamine or veneered frame.
INTERIOR	Acoustic panel on the ceiling. Walls x 2 and floor coated with carpet.
DOOR	Painted MDF door. Melamine door side panels. Door handle with satin finished stainless steel.
WINDOW	Laminated acoustic safety glass window 10 mm. Glass window includes the INTO stripe window taping.
TABLE	MDF table with water-based paint.

ADD-ON FEATURES

POD PANEL

POD PANEL is an acoustic-friendly add-on piece for POD rooms. It can be used as a surface to attach notes, plans, and other sketches. Panels attaches easily to the POD exterior and softens the surrounding sound environment.



OTHER AVAILABLE ADD-ON FEATURES

Height adjustable stool
Clothing hook
Eletronical lock system
Booking system
Smart glass
Screen holder
USB charger
Extra power sockets
AV systems (web camera, microphone)
Automatic fire extinguisher system

INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.

INTO
the Nordic Silence

All our materials comply with M1 emission classification.

SURFACE FINISHES FOR POD ROOMS

STANDARD PRICE, CATEGORY 1

Melamine color options

White

Dark grey

PRICE CATEGORY 2

Veneer options



Pine



American oak



Black oak

SURFACE FINISHES FOR DOOR & DOOR SIDE PANELS

STANDARD PRICE, CATEGORY 1

White

PRICE CATEGORY 2



American oak



Clear glass 10 mm

comes with white door panels

CARPETS FOR POD ROOMS: EX-DONO QUARTET FROM FLETCO | STANDARD PRICE, CATEGORY 1

Composition: Polyester non woven
Static electrical propensity: Antistatic
Impact sound reduction: 25 dB
Classification for use: Commercial / heavy use
Fire resistant: Yes



393300




393340



393350

Ask for more colors: sales@intoconcept.com





CEILING ACOUSTIC PANEL FABRIC: SOUL FROM GABRIEL | STANDARD PRICE, CATEGORY 1

Composition: 100% wool
Lightfastness: 5-7
Rubbing fastness: 4/wet, 4-5/dry
Sustainability: Complies with STANDARD 100 by OEKO-TEX
Meet Möbelfakta requirements
Cleaning: regular vacuum cleaning
Fire resistant: Yes (S 476 Part 7, class 1 ÖNORM B 3825-B1-3800-Q1 UK)



66104



67039



68131




64086



62059



61196



60182

OEKO-TEX®
CONFIDENCE IN TEXTILES
STANDARD 100

10 year guarantee against wearing through

INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.

INTO
the Nordic Silence



POD PHONE


POD PHONE is a phone booth that improves privacy when taking phone calls in open spaces and office environments.

TECHNICAL INFORMATION

AIR FLOW	Fully automated ventilation controlled by motion sensor. As standard, set to 1 hour and is adjustable up to 99 minutes. Air flow 22l/s.
LIGHTS	Fully automated lights controlled by motion sensor. As standard, set to 1 hour and is adjustable up to 99 minutes. LED light set on the ceiling. Lumen 871.
WHEELS	Installation wheels included.
ENERGY CONSUMPTION PER HOUR	Total 0,01895 kWh. Fans 0,00445 kWh. Lights 0,0145 kWh. Max load 8 A.
SOCKET	One power socket on the table.
POWER CONNECTION	From the ceiling or floor. The length of the power cord is 3 m.

MEASUREMENTS

EXTERNAL DIMENSIONS	W1000 x D1500 x H2220 mm
INNER DIMENSIONS	W800 x D1100 x H2040 mm
DOOR	8 x 21
PACKAGE DIMENSIONS	W800 x D2400 x H1500 mm
WEIGHT	460 kg 307 kg/m2



INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.

INTO
the Nordic Silence

MATERIAL DESCRIPTION

EXTERIOR	Melamine or veneered frame.
INTERIOR	Acoustic panel on the ceiling. Walls x 2 and floor coated with carpet.
DOOR	Painted MDF door. Melamine door side panels. Door handle with satin finished stainless steel.
WINDOW	Laminated acoustic safety glass window 10 mm. Glass window includes the INTO stripe window taping.
TABLE	MDF table with water-based paint.

ADD-ON FEATURES

POD PANEL

POD PANEL is an acoustic-friendly add-on piece for POD rooms. It can be used as a surface to attach notes, plans, and other sketches. Panels attaches easily to the POD exterior and softens the surrounding sound environment.



OTHER AVAILABLE ADD-ON FEATURES

Height adjustable stool
Clothing hook
Eletronical lock system
Booking system
Smart glass
Screen holder
USB charger
Extra power sockets
AV systems (web camera, microphone)
Automatic fire extinguisher system

INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.


INTO
the Nordic Silence

All our materials comply with M1 emission classification.

SURFACE FINISHES FOR POD ROOMS

STANDARD PRICE, CATEGORY 1

Melamine color options


White


Dark grey

PRICE CATEGORY 2

Veneer options



Pine


American oak


Black oak

SURFACE FINISHES FOR DOOR & DOOR SIDE PANELS

STANDARD PRICE, CATEGORY 1


White

PRICE CATEGORY 2


American oak


Clear glass 10 mm

comes with white door panels

CARPETS FOR POD ROOMS: EX-DONO QUARTET FROM FLETCO | STANDARD PRICE, CATEGORY 1

Composition: Polyester non woven
Static electrical propensity: Antistatic
Impact sound reduction: 25 dB
Classification for use: Commercial / heavy use
Fire resistant: Yes



393300


393340


393350

Ask for more colors: sales@intoconcept.com





CEILING ACOUSTIC PANEL FABRIC: SOUL FROM GABRIEL | STANDARD PRICE, CATEGORY 1

Composition: 100% wool
Lightfastness: 5-7
Rubbing fastness: 4/wet, 4-5/dry
Sustainability: Complies with STANDARD 100 by OEKO-TEX
Meet Möbelfakta requirements
Cleaning: regular vacuum cleaning
Fire resistant: Yes (S 476 Part 7, class 1 ÖNORM B 3825-B1-3800-Q1 UK)


66104



67039


68131


64086


62059


61196


60182

OEKO-TEX®
CONFIDENCE IN TEXTILES
STANDARD 100

10 year guarantee against wearing through

INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.

INTO
the Nordic Silence



POD 1


POD 1 is the number one choice for private phone calls and a workspace for tasks which demand focusing.

TECHNICAL INFORMATION

AIR FLOW	Fully automated ventilation controlled by motion sensor. As standard, set to 1 hour and is adjustable up to 99 minutes. Switch for ventilation. Air flow 22 l/s.
LIGHTS	Fully automated lights controlled by motion sensor. As standard, set to 1 hour and is adjustable up to 99 minutes. Switch for lights. 2 x LED light set on the ceiling. A window lamp. Lumen 1742.
WHEELS	Installation wheels included.
ENERGY CONSUMPTION PER HOUR	Total 0,04045 kWh. Fans 0,00445 kWh. Lights 0,036 kWh. Max load 8 A.
SOCKET	3 x power sockets + 1 x data outlet included
POWER CONNECTION	From the ceiling or floor. The length of the power cord is 3 m.

MEASUREMENTS

EXTERNAL DIMENSIONS	W1700 x D1700 x H2220 mm
DOOR	9 x 21
INNER DIMENSIONS	W1500 x D1300 x H2040 mm
PACKAGE DIMENSIONS	W1200 x D2400 x H1500 mm
WEIGHT	690 kg 239kg/m2



INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.

INTO
the Nordic Silence


MATERIAL DESCRIPTION

EXTERIOR	Melamine or veneered frame.
INTERIOR	Acoustic panel on the ceiling. Back wall and floor coated with carpet.
DOOR	Painted MDF door. Melamine door side panels. Door handle with satin finished stainless steel.
WINDOW	Laminated acoustic safety glass window 10 mm. Glass window includes the INTO stripe window taping.

ADD-ON FEATURES

POD PANEL

POD PANEL is an acoustic-friendly add-on piece for POD rooms. It can be used as a surface to attach notes, plans, and other sketches. Panels attaches easily to the POD exterior and softens the surrounding sound environment.





ACCESSIBILITY SET

Wheelchair ramp.
Reservation for automatic door.
Automatic door closer.
Hydraulic door closer.
Kick-plates for the door and/or walls.
Vertical and/or horizontal bar handles.





FURNITURE SET

Furnish the POD room with INTO sofas and tables.
For example: 2 x POINT 700, TOP LIFT HIGH 400 x 600.



OTHER AVAILABLE ADD-ON FEATURES

Clothing hook
Eletronical lock system
Booking system
Smart glass
USB charger
Extra power sockets
AV systems (web camera, microphone)
Automatic fire extinguisher system

INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.

INTO
the Nordic Silence

All our materials comply with M1 emission classification.

SURFACE FINISHES FOR POD ROOMS

STANDARD PRICE, CATEGORY 1

Melamine color options

White

Dark grey

PRICE CATEGORY 2

Veneer options



Pine



American oak



Black oak

SURFACE FINISHES FOR DOOR & DOOR SIDE PANELS

STANDARD PRICE, CATEGORY 1

White

PRICE CATEGORY 2



American oak



Clear glass 10 mm

comes with white door panels

CARPETS FOR POD ROOMS: EX-DONO QUARTET FROM FLETCO | STANDARD PRICE, CATEGORY 1

Composition: Polyester non woven
Static electrical propensity: Antistatic
Impact sound reduction: 25 dB
Classification for use: Commercial / heavy use
Fire resistant: Yes



393300




393340



393350

Ask for more colors: sales@intoconcept.com





CEILING ACOUSTIC PANEL FABRIC: SOUL FROM GABRIEL | STANDARD PRICE, CATEGORY 1

Composition: 100% wool
Lightfastness: 5-7
Rubbing fastness: 4/wet, 4-5/dry
Sustainability: Complies with STANDARD 100 by OEKO-TEX
Meet Möbelfakta requirements
Cleaning: regular vacuum cleaning
Fire resistant: Yes (S 476 Part 7, class 1 ÖNORM B 3825-B1-3800-Q1 UK)



66104



67039



68131




64086



62059



61196



60182

OEKO-TEX®
CONFIDENCE IN TEXTILES
STANDARD 100

10 year guarantee against wearing through

INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.

INTO
the Nordic Silence



POD 2


The POD 2 small meeting room is ideal for 2-4 people for spontaneous but confidential meetings and as an adaptable workspace.

TECHNICAL INFORMATION

AIR FLOW	Fully automated ventilation controlled by motion sensor. As standard, set to 1 hour and is adjustable up to 99 minutes. Switch for ventilation. Air flow 44 l/s.
LIGHTS	Fully automated lights controlled by motion sensor. As standard, set to 1 hour and is adjustable up to 99 minutes. Switch for lights. 2 x LED light set on the ceiling. A window lamp. Lumen 1742.
WHEELS	Installation wheels included.
ENERGY CONSUMPTION PER HOUR	Total 0,0449 kWh. Fans 0,0089 kWh. Lights 0,036 kWh. Max load 8 A.
SOCKET	3 x power sockets + 2 x data outlets included.
POWER CONNECTION	From the ceiling or floor. The length of the power cord is 3 m.

MEASUREMENTS

EXTERNAL DIMENSIONS	W2500 x D1700 x H2220 mm
DOOR	9 x 21
INNER DIMENSIONS	W2300 x D1300 x H2040 mm
PACKAGE DIMENSIONS	W1200 x D2520x H1500 mm
WEIGHT	910 kg 214 kg/m2



INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.

INTO
the Nordic Silence


MATERIAL DESCRIPTION

EXTERIOR	Melamine or veneered frame.
INTERIOR	Acoustic panel on the ceiling. Back wall and floor coated with carpet.
DOOR	Painted MDF door. Melamine door side panels. Door handle with satin finished stainless steel.
WINDOW	Laminated acoustic safety glass window 10 mm. Glass window includes the INTO stripe window taping.

ADD-ON FEATURES

POD PANEL

POD PANEL is an acoustic-friendly add-on piece for POD rooms. It can be used as a surface to attach notes, plans, and other sketches. Panels attaches easily to the POD exterior and softens the surrounding sound environment.



FURNITURE SET

Furnish the POD room with INTO sofas and tables.
For example: 1 x POINT 700, 2 x POINT 500,
TOP LIFT HIGH 600 x 800.



ACCESSIBILITY SET

Wheelchair ramp.
Reservation for automatic door.
Automatic door closer.
Hydraulic door closer.
Kick-plates for the door and/or walls.
Vertical and/or horizontal bar handles.





OTHER AVAILABLE ADD-ON FEATURES

Clothing hook
Eletronical lock system
Booking system
Smart glass
USB charger
Extra power sockets
AV systems (web camera, microphone)
Automatic fire extinguisher system

INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.


INTO
the Nordic Silence

All our materials comply with M1 emission classification.

SURFACE FINISHES FOR POD ROOMS

STANDARD PRICE, CATEGORY 1

Melamine color options


White


Dark grey

PRICE CATEGORY 2

Veneer options



Pine


American oak


Black oak

SURFACE FINISHES FOR DOOR & DOOR SIDE PANELS

STANDARD PRICE, CATEGORY 1


White

PRICE CATEGORY 2


American oak


Clear glass 10 mm

comes with white door panels

CARPETS FOR POD ROOMS: EX-DONO QUARTET FROM FLETCO | STANDARD PRICE, CATEGORY 1

Composition: Polyester non woven
Static electrical propensity: Antistatic
Impact sound reduction: 25 dB
Classification for use: Commercial / heavy use
Fire resistant: Yes



393300


393340


393350

Ask for more colors: sales@intoconcept.com





CEILING ACOUSTIC PANEL FABRIC: SOUL FROM GABRIEL | STANDARD PRICE, CATEGORY 1

Composition: 100% wool
Lightfastness: 5-7
Rubbing fastness: 4/wet, 4-5/dry
Sustainability: Complies with STANDARD 100 by OEKO-TEX
Meet Möbelfakta requirements
Cleaning: regular vacuum cleaning
Fire resistant: Yes (S 476 Part 7, class 1 ÖNORM B 3825-B1-3800-Q1 UK)


66104



67039


68131


64086


62059


61196


60182

OEKO-TEX®
CONFIDENCE IN TEXTILES
STANDARD 100

10 year guarantee against wearing through

INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.

INTO
the Nordic Silence



POD 4


POD 4 meeting rooms are suitable for 4-8 people and perfect for private or confidential meetings as well as adaptable work spaces.

TECHNICAL INFORMATION

AIR FLOW	Fully automated ventilation controlled by motion sensor. As standard, set to 1 hour and is adjustable up to 99 minutes. Switch for ventilation. Air flow 88l/s.
LIGHTS	Fully automated lights controlled by motion sensor. As standard, set to 1 hour and is adjustable up to 99 minutes. Switch for lights. 4 x LED light set on the ceiling. 1 window lamp. Lumen 3484.
WHEELS	Installation wheels included.
ENERGY CONSUMPTION PER HOUR	Total 0,0828 kWh. Fans 0,0178 kWh. Lights 0,065 kWh. Max load 8 A.
SOCKET	4 x power sockets + 2 x data outlets included.
POWER CONNECTION	From the ceiling or floor. The length of the power cord is 3 m.

MEASUREMENTS

EXTERNAL DIMENSIONS	W3400 x D2500 x H2220 mm
DOOR	9 x 21
INNER DIMENSIONS	W3200 x D2100 x H2040 mm
PACKAGE DIMENSIONS	2 x pallet: W1200 x L2520 x H1500 and W1200 x L2400 x H1500
WEIGHT	1450 kg 171 kg/m2



INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.

INTO
the Nordic Silence

MATERIAL DESCRIPTION

EXTERIOR	Melamine or veneered frame.
INTERIOR	Acoustic panels on the ceiling. Back wall and floor coated with carpet.
DOOR	Painted MDF door. Melamine door side panels. Door handle with satin finished stainless steel.
WINDOW	Laminated acoustic safety glass window 10 mm. Glass window includes the INTO stripe window taping.

ADD-ON FEATURES


DISPLAY BOX

DISPLAY BOX is a screen stand for the POD meeting rooms that hides the cables and the remote control. Suitable for a maximum 42" screen.



POD PANEL

POD PANEL is an acoustic-friendly add-on piece for POD rooms. It can be used as a surface to attach notes, plans, and other sketches. Panels attaches easily to the POD exterior and softens the surrounding sound environment.





ACCESSIBILITY SET

Wheelchair ramp.
Reservation for automatic door.
Automatic door closer.
Hydraulic door closer.
Kick-plates for the door and/or walls.
Vertical and/or horizontal bar handles.





FURNITURE SET

Furnish the POD room with INTO sofas and tables.
For example; 4 x POINT 700, 1 x POINT CORNER,
2 x TOP CURVE, 1 x DISPLAY BOX



OTHER ADD-ON FEATURES

Clothing hook
Eletronical lock system
Booking system
Smart glass
USB charger
Extra power sockets
AV systems (web camera, microphone)
Automatic fire extinguisher system

INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.

INTO
the Nordic Silence

All our materials comply with M1 emission classification.

SURFACE FINISHES FOR POD ROOMS

STANDARD PRICE, CATEGORY 1

Melamine color options

White

Dark grey

PRICE CATEGORY 2

Veneer options



Pine



American oak



Black oak

SURFACE FINISHES FOR DOOR & DOOR SIDE PANELS

STANDARD PRICE, CATEGORY 1

White

PRICE CATEGORY 2



American oak



Clear glass 10 mm

comes with white door panels

CARPETS FOR POD ROOMS: EX-DONO QUARTET FROM FLETCO | STANDARD PRICE, CATEGORY 1

Composition: Polyester non woven
Static electrical propensity: Antistatic
Impact sound reduction: 25 dB
Classification for use: Commercial / heavy use
Fire resistant: Yes



393300




393340



393350

Ask for more colors: sales@intoconcept.com





CEILING ACOUSTIC PANEL FABRIC: SOUL FROM GABRIEL | STANDARD PRICE, CATEGORY 1

Composition: 100% wool
Lightfastness: 5-7
Rubbing fastness: 4/wet, 4-5/dry
Sustainability: Complies with STANDARD 100 by OEKO-TEX
Meet Möbelfakta requirements
Cleaning: regular vacuum cleaning
Fire resistant: Yes (S 476 Part 7, class 1 ÖNORM B 3825-B1-3800-Q1 UK)



66104



67039



68131




64086



62059



61196



60182

OEKO-TEX®
CONFIDENCE IN TEXTILES
STANDARD 100

10 year guarantee

INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.

INTO
the Nordic Silence



POD ROLL

POD ROLL is a compact solution for spontaneous meetings and independent work.


TECHNICAL INFORMATION

Solution includes POINT sofas, table, ceiling lamp, power sockets, and wheels.

LIGHTS	Fully automated lights with electronic motion sensor. Switch for lights. Ceiling light. Lumen 2100.
WHEELS	Wheels under the POD ROLL makes it easy to turn and move around if needed.
ENERGY CONSUMPTION PER HOUR	Total 0,014 kWh. Lights 0,014 kWh. Max load 8 A.
SOCKET	One power socket on the tabletop + 3 under the table.
POWER CONNECTION	From the ceiling or floor. The length of the power cord is 3 m.

MEASUREMENTS

EXTERNAL DIMENSIONS	W2300 x D1700 x H2220 mm
INNER DIMENSIONS	W2000 x D1640 x H1980 mm
TABLE	W700 x D1100 x H730 mm
PACKAGE DIMENSIONS	2 x pallet: W1000 x D2500 x H1500 mm and W850 x D1700 x H2000 mm
WEIGHT	700 kg 179 kg/m2



INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.

INTO
the Nordic Silence

All our materials comply with M1 emission classification.

MATERIAL DESCRIPTION

EXTERIOR	Melamine frame.
INTERIOR	Floor coated with carpet. Ceiling and wall covered with upholstered acoustic panels.
TABLE	MDF table with structural painted top and powder coated steel base.
WINDOW	Laminated acoustic safety glass window 10 mm. Glass window includes the INTO stripe window taping.

SURFACE FINISHES FOR POD ROLL | STANDARD PRICE, CATEGORY 1

Melamine color options

White Dark grey

CARPETS FOR POD ROOMS: EX-DONO QUARTET FROM FLETCO | STANDARD PRICE, CATEGORY 1

Composition: Polyester non woven
Static electrical propensity: Antistatic
Impact sound reduction: 25 dB
Classification for use: Commercial / heavy use
Fire resistant: Yes

393300 393340 393350

CE
EN 14041:2004
17
2531-CPR-CXA10107
C_{fl}-s1 NPD

COLOR OPTIONS FOR POD ROLL TABLE | STANDARD PRICE, CATEGORY 1

TABLE TOP

NCS S 0500-N
Structural

STEEL TUBE BASE

RAL 9016
white


Ask for more colors: sales@intoconcept.com

INTO
the Nordic Silence

Ask for more colors: sales@intoconcept.com

SOFA FABRIC FOR POD ROLL: MAIN LINE FLAX FROM CAMIRA | STANDARD PRICE, CATEGORY 1


Composition: 70% Virgin wool, 30% Flax
Durability: 50.000 Martindale
Light fastness: 5
Crocking: 3/wet, 4/dry
Sustainability: Complies with EU ecolabel “The Flower”, Compostable
Cleaning: Vacuuming and dry cleaning
Fire resistant: Yes



MLF02 MLF14 MLF16 MLF19 MLF24 MLF67 MLF37

SOFA FABRIC FOR POD ROLL: PYTON FROM DELFOS FR | PRICE CATEGORY 2

Synthetic leather
Composition: 77% PVC, 23% CO
Abrasion / Martindale: dry = 51.200 /cycles, wet = 12.800 /cycles
Light fastness: 5
Crocking: 4-5
Breathable
Fire resistant: Yes / Flame retardant, IMO Certificate



0796 Negro 1112 Smoke 0793 Mocca 1168 Cashmere

Cleaning:
Because of its characteristics, clean and care the material frequently, with lukewarm water and a damp cloth, preferably of micro fibre. Soiling may be treated with a mild soap and proceed next to its drying by using a hairdryer or, failing that, a drymcloth. It should be avoided that areas that have been treated for cleaning remain wet



breathable and flame retardant quality | efficient material | long-life | easy-to-clean | aesthetic value

SOFA FABRIC FOR POD ROLL: SYNERGY FROM CAMIRA | PRICE CATEGORY 2


Composition: 95% Virgin wool, 5% Polyamide
Durability: 100.000 Martindale
Pilling: 4
Light fastness: 5
Cleaning: vacuuming and dry cleaning
Fire resistant: Yes



LDS08 LDS16 LDS17 LDS48 LDS56 LDS59 LDS87

SOFA FABRIC FOR POD ROLL: GRAIN/2288 FROM GABRIEL | PRICE CATEGORY 2

Composition: 80% post-consumer recycled polyester / 20% polyester
Durability: 100.000 Martindale
Pilling: 5
Light fastness: 5-7
Cleaning: wash or dry cleaning
Fire resistant: Yes



61247 62123 64251 66233 68258 60323

INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.

INTO
the Nordic Silence



POD ROLL GLASS

POD ROLL GLASS is perfect for ad hoc meetings, work that needs focusing and as a space divider and added seating space.


TECHNICAL INFORMATION

Solution includes POINT sofas, table, ceiling lamp, power sockets, and wheels.

AIR FLOW	Fully automated ventilation with electronic motion sensor. Switch for ventilation. Air flow 44l/s.
LIGHTS	Fully automated lights with electronic motion sensor. Switch for lights. Ceiling light. Lumen 2100.
WHEELS	Wheels under the POD ROLL makes it easy to turn and move around if needed.
ENERGY CONSUMPTION PER HOUR	Total 0,0229 kWh. Fans 0,089 kWh. Lights 0,014 kWh. Max load 8 A.
SOCKET	One power socket on the tabletop + 3 under the table.
POWER CONNECTION	From the ceiling or floor. The length of the power cord is 3 m.

MEASUREMENTS

EXTERNAL DIMENSIONS	W2300 x D1700 x H2220 mm
INNER DIMENSIONS	W2000 x D1640 x H1980 mm
TABLE	W700 x D1100 x H730 mm
PACKAGE DIMENSIONS	2 x pallet: W1200 x D2500 x H1500 mm and W850 x D1700 x H2000 mm
WEIGHT	800 kg 205 kg/m2



INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.

INTO
the Nordic Silence

All our materials comply with M1 emission classification.

MATERIAL DESCRIPTION

EXTERIOR	Melamine frame.
INTERIOR	Floor coated with carpet. Ceiling and wall covered with upholstered acoustic panels.
TABLE	MDF table with structural painted top and powder coated steel base.
WINDOW	Laminated acoustic safety glass window 10 mm. Glass window includes the INTO stripe window taping.
DOOR	Clear glass 10 mm. Door handle with satin finished stainless steel.

SURFACE FINISHES FOR POD ROLL GLASS| STANDARD PRICE, CATEGORY 1

Melamine color options

White Dark grey

CARPETS FOR POD ROOMS: EX-DONO QUARTET FROM FLETCO | STANDARD PRICE, CATEGORY 1

Composition: Polyester non woven
Static electrical propensity: Antistatic
Impact sound reduction: 25 dB
Classification for use: Commercial / heavy use
Fire resistant: Yes

393300 393340 393350

EN 14041:2004
17
2531-CPR-CXA10107

COLOR OPTIONS FOR POD ROLL GLASS TABLE | STANDARD PRICE, CATEGORY 1

TABLE TOP

NCS S 0500-N
Structural

STEEL TUBE BASE

RAL 9016
white


Ask for more colors: sales@intoconcept.com

INTO
the Nordic Silence

Ask for more colors: sales@intoconcept.com

SOFA FABRIC FOR POD ROLL GLASS: MAIN LINE FLAX FROM CAMIRA | STANDARD PRICE, CATEGORY 1


Composition: 70% Virgin wool, 30% Flax
Durability: 50.000 Martindale
Lightfastness: 5
Crocking: 3/wet, 4/dry
Sustainability: Complies with EU ecolabel “The Flower”, Compostable
Cleaning: Vacuuming and dry cleaning
Fire resistant: Yes



MLF02 MLF14 MLF16 MLF19 MLF24 MLF67 MLF37

SOFA FABRIC FOR POD ROLL GLASS: PYTON FROM DELFOS FR | PRICE CATEGORY 2

Synthetic leather
Composition: 77% PVC, 23% CO
Abrasion / Martindale: dry = 51.200 /cycles, wet = 12.800 /cycles
Lightfastness: 5
Crocking: 4-5
Breathable
Fire resistant: Yes / Flame retardant, IMO Certificate



0796 Negro 1112 Smoke 0793 Mocca 1168 Cashmere

Cleaning:
Because of its characteristics, clean and care the material frequently, with lukewarm water and a damp cloth, preferably of micro fibre. Soiling may be treated with a mild soap and proceed next to its drying by using a hairdryer or, failing that, a drymcloth. It should be avoided that areas that have been treated for cleaning remain wet



breathable and flame retardant quality | efficient material | long-life | easy-to-clean | aesthetic value

SOFA FABRIC FOR POD ROLL GLASS: SYNERGY FROM CAMIRA | PRICE CATEGORY 2


Composition: 95% Virgin wool, 5% Polyamide
Durability: 100.000 Martindale
Pilling: 4
Lightfastness: 5
Cleaning: vacuuming and dry cleaning
Fire resistant: Yes



LDS08 LDS16 LDS17 LDS48 LDS56 LDS59 LDS87

SOFA FABRIC FOR POD ROLL GLASS: GRAIN/2288 FROM GABRIEL | PRICE CATEGORY 2

Composition: 80% post-consumer recycled polyester / 20% polyester
Durability: 100.000 Martindale
Pilling: 5
Light fastness: 5-7
Cleaning: wash or dry cleaning
Fire resistant: Yes



61247 62123 64251 66233 68258 60323

OEKO-TEX® CONFIDENCE IN TEXTILES STANDARD 100

INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.


INTO
the Nordic Silence



POD PANEL

POD Panel is an acoustic-friendly add-on piece for POD rooms. The panels are easy to attach and detach with their effortless fastening system. They can also be used as a surfaces to attach notes, plans, and other sketches important for your team and their tasks.

TECHNICAL INFORMATION	Easy to attach and detach with effortless fastening system.
MATERIAL DESCRIPTION	Plywood frame with acoustic wool. Fully upholstered.
MEASUREMENTS	W500/600 x D45 x H2220 mm



ACOUSTIC PANEL FABRIC: SOUL FROM GABRIEL | STANDARD PRICE, CATEGORY 1

Composition: 100% wool
Lightfastness: 5-7
Rubbing fastness: 4/wet, 4-5/dry
Sustainability: Complies with STANDARD 100 by OEKO-TEX
Meet Möbelfakta requirements
Cleaning: regular vacuum cleaning
Fire resistant: Yes (S 476 Part 7, class 1 ÖNORM B 3825-B1-3800-Q1 UK)

M1 EMISSION CLASS FOR BUILDING MATERIAL

All our materials comply with M1 emission classification.



66104 67039 68131 64086 62059 61196 60182

OEKO-TEX® CONFIDENCE IN TEXTILES STANDARD 100

10 year guarantee against wearing through

INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.

INTO
the Nordic Silence

WHEELCHAIR RAMP



In accordance with accessibility standards, a wheelchair ramp can be installed into the POD rooms, as well as reservation for the automatic door.

TECHNICAL INFORMATION	Available for POD rooms 1-4.
MATERIAL DESCRIPTION	Powder-coated steel with grip tape.
MEASUREMENTS	According to the door width.

STANDARD COLOR FOR WHEELCHAIR RAMP

STANDARD PRICE, CATEGORY 1

RAL 9016
white

RAL 7005
grey

Ask for more colors!

INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.


INTO
the Nordic Silence



DISPLAY BOX

DISPLAY BOX is a screen holder specially designed for the POD meeting rooms. This screen holder is not only stylish but also makes it possible to hide the disruptive cables and remote control.

TECHNICAL INFORMATION	Three electrical sockets. TV screen and the wall mount brackets are not included.
MATERIAL DESCRIPTION	MDF board with water-based paint.
MEASUREMENTS	Up to 42” screen: W700 x D100 x H1400 mm



SURFACE FINISHES FOR DISPLAY BOX:

NCS S 9000-N
Structural

All our materials comply with M1 emission classification.

INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.

INTO
the Nordic Silence





CUBE

CUBE is a sheltered sofa that is recommended to place two facing each other, in which case the sofas form an acoustically pleasant environment.

MATERIAL DESCRIPTION


Frame is fully upholstered with fabric.
Seat and backrest upholstered polyurethane foam.
Powder-coated steel tube base.

OPTIONS

An optional armrest with electrical socket is available.

MEASUREMENTS

W1600 x D720 x H1600 mm



INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.

INTO
the Nordic Silence

All our materials comply with M1 emission classification.


CUBE ARMREST



TECHNICAL INFORMATION	Built-in electrical socket. The length of the electric cord is 3 m.
MATERIAL DESCRIPTION	Veneer structure. Upholstered with fabric.
MEASUREMENTS	W155 x D340 x H260 mm

SOFA FABRIC FOR CUBE: MAIN LINE FLAX FROM CAMIRA | STANDARD PRICE, CATEGORY 1


Composition: 70% Virgin wool, 30% Flax
Durability: 50.000 Martindale
Lightfastness: 5
Crocking: 3/wet, 4/dry
Sustainability: Complies with EU ecolabel “The Flower”, Compostable
Cleaning: Vacuuming and dry cleaning
Fire resistant: Yes



MLF02 MLF14 MLF16 MLF19 MLF24 MLF67 MLF37

SOFA FABRIC FOR CUBE: PYTON FROM DELFOS FR | PRICE CATEGORY 2

Synthetic leather
Composition: 77% PVC, 23% CO
Abrasion / Martindale: dry = 51.200 /cycles, wet = 12.800 /cycles
Lightfastness: 5
Crocking: 4-5
Breathable
Fire resistant: Yes / Flame retardant, IMO Certificate



0796 Negro 1112 Smoke 0793 Mocca 1168 Cashmere

Cleaning:
Because of its characteristics, clean and care the material frequently, with lukewarm water and a damp cloth, preferably of micro fibre. Soiling may be treated with a mild soap and proceed next to its drying by using a hairdryer or, failing that, a drymcloth. It should be avoided that areas that have been treated for cleaning remain wet



breathable and flame retardant quality | efficient material | long-life | easy-to-clean | aesthetic value

SOFA FABRIC FOR CUBE: SYNERGY FROM CAMIRA | PRICE CATEGORY 2

Composition: 95% Virgin wool, 5% Polyamide
Durability: 100.000 Martindale
Pilling: 4
Lightfastness: 5
Cleaning: vacuuming and dry cleaning
Fire resistant: Yes



LDS08 LDS16 LDS17 LDS48 LDS56 LDS59 LDS87


INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.

INTO
the Nordic Silence

Ask for more colors: sales@intoconcept.com

SOFA FABRIC FOR CUBE: GRAIN/2288 FROM GABRIEL | PRICE CATEGORY 2

Composition: 80% post-consumer recycled polyester / 20% polyester
Durability: 100.000 Martindale
Pilling: 5
Light fastness: 5-7
Cleaning: wash or dry cleaning
Fire resistant: Yes




61247 62123 64251 66233 68258 60323

OEKO-TEX®
CONFIDENCE IN TEXTILES
STANDARD 100

10 year guarantee


INTO
the Nordic Silence



CUBE SOLO

CUBE SOLO is a rotating swivel chair that provides privacy within an acoustically friendly and comfortable environment. Adding a TOP table turns the chair to a peaceful working area.

MATERIAL DESCRIPTION	Upholstered with fabric. Seat and backrest upholstered polyurethane foam. Powder-coated steel tube base.
OPTIONS	An optional armrest with electrical socket is available.
MEASUREMENTS	W800 x D720 x H1600 mm



INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.

INTO
the Nordic Silence

All our materials comply with M1 emission classification.


CUBE SOLO ARMREST



TECHNICAL INFORMATION	Built-in electrical socket. The length of the electric cord is 3 m.
MATERIAL DESCRIPTION	Veneer structure. Upholstered with fabric.
MEASUREMENTS	W155 x D340 x H260 mm

SOFA FABRIC FOR CUBE SOLO: MAIN LINE FLAX FROM CAMIRA | STANDARD PRICE, CATEGORY 1


Composition: 70% Virgin wool, 30% Flax
Durability: 50.000 Martindale
Lightfastness: 5
Crocking: 3/wet, 4/dry
Sustainability: Complies with EU ecolabel “The Flower”, Compostable
Cleaning: Vacuuming and dry cleaning
Fire resistant: Yes



MLF02 MLF14 MLF16 MLF19 MLF24 MLF67 MLF37

SOFA FABRIC FOR CUBE SOLO: PYTON FROM DELFOS FR | CATEGORY 2

Synthetic leather
Composition: 77% PVC, 23% CO
Abrasion / Martindale: dry = 51.200 /cycles, wet = 12.800 /cycles
Lightfastness: 5
Crocking: 4-5
Breathable
Fire resistant: Yes / Flame retardant, IMO Certificate



0796 Negro 1112 Smoke 0793 Mocca 1168 Cashmere

Cleaning:
Because of its characteristics, clean and care the material frequently, with lukewarm water and a damp cloth, preferably of micro fibre. Soiling may be treated with a mild soap and proceed next to its drying by using a hairdryer or, failing that, a drymcloth. It should be avoided that areas that have been treated for cleaning remain wet



breathable and flame retardant quality | efficient material | long-life | easy-to-clean | aesthetic value

SOFA FABRIC FOR CUBE SOLO: SYNERGY FROM CAMIRA | CATEGORY 2

Composition: 95% Virgin wool, 5% Polyamide
Durability: 100.000 Martindale
Pilling: 4
Lightfastness: 5
Cleaning: vacuuming and dry cleaning
Fire resistant: Yes




LDS08 LDS16 LDS17 LDS48 LDS56 LDS59 LDS87

INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.

INTO
the Nordic Silence

SOFA FABRIC FOR CUBE SOLO: GRAIN/2288 FROM GABRIEL | PRICE CATEGORY 2

Composition: 80% post-consumer recycled polyester / 20% polyester
Durability: 100.000 Martindale
Pilling: 5
Light fastness: 5-7
Cleaning: wash or dry cleaning
Fire resistant: Yes



61247 62123 64251 66233 68258 60323

OEKO-TEX®
CONFIDENCE IN TEXTILES
STANDARD 100

10 year guarantee

Ask for more colors: sales@intoconcept.com

INTO
the Nordic Silence



POINT SOFAS

POINT office sofa consists of individual sofa modules made of durable and comfortable materials that can be combined to create countless sofa combinations.

TECHNICAL INFORMATION

The office sofa modules are available with both low and high backrests and the seating measurements support healthy working positions.
Connectors included.

MATERIAL DESCRIPTION


Plywood base and frame.
Polyurethane foam.
Fabric upholstery.
Base color painted grey.


OPTIONS

Integrated electrical sockets with the power cord length 5 m.
POINT sofas are available with lockable wheels.

MEASUREMENTS

POINT:	W500/700/1000 x D700 x H920/1420 mm
POINT STOOL:	W500/700 x D700 x H470 mm
POINT CORNER:	W700 x D700 x H920/1420 mm
POINT CURVE IN:	W1020 x D700 x H920/1420 mm
POINT CURVE OUT:	W1020 x D700 x H920/1420 mm
POINT OUTER CORNER, Left/Right:	W1100 x D700 x H920/1420 mm
Seat height:	470 mm
Seat height with wheels:	480 mm






INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.


INTO
the Nordic Silence

POINT SOFAS - COMBINING EXAMPLES







CURVE IN x 4




CURVE OUT x 6




OUTER CORNER x 4




OUTER CORNER x 4
LONG x 2




MEDIUM x 1
LONG x 2
STOOL x 1



CORNER x 2
SMALL x 2



CORNER x 3
SMALL x 2



CURVE IN x 2
CURVE OUT x 2
MEDIUM x 2


INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.

INTO
the Nordic Silence

All our materials comply with M1 emission classification.

UPHOLSTERY FABRIC: MAIN LINE FLAX FROM CAMIRA | STANDARD PRICE, CATEGORY 1


Composition: 70% Virgin wool, 30% Flax
Durability: 50.000 Martindale
Lightfastness: 5
Crocking: 3/wet, 4/dry
Sustainability: Complies with EU ecolabel “The Flower”, Compostable
Cleaning: Vacuuming and dry cleaning
Fire resistant: Yes



MLF02 MLF14 MLF16 MLF19 MLF24 MLF67 MLF37

UPHOLSTERY FABRIC: PYTON FROM DELFOS FR | CATEGORY 2

Synthetic leather
Composition: 77% PVC, 23% CO
Abrasion / Martindale: dry = 51.200 /cycles, wet = 12.800 /cycles
Lightfastness: 5
Crocking: 4-5
Breathable
Fire resistant: Yes / Flame retardant, IMO Certificate



0796 Negro 1112 Smoke 0793 Mocca 1168 Cashmere

Cleaning:
Because of its characteristics, clean and care the material frequently, with lukewarm water and a damp cloth, preferably of micro fibre. Soiling may be treated with a mild soap and proceed next to its drying by using a hairdryer or, failing that, a drymcloth. It should be avoided that areas that have been treated for cleaning remain wet



breathable and flame retardant quality | efficient material | long-life | easy-to-clean | aesthetic value

UPHOLSTERY FABRIC: SYNERGY FROM CAMIRA | CATEGORY 2


Composition: 95% Virgin wool, 5% Polyamide
Durability: 100.000 Martindale
Pilling: 4
Lightfastness: 5
Cleaning: vacuuming and dry cleaning
- Fire resistant: Yes



LDS08 LDS16 LDS17 LDS48 LDS56 LDS59 LDS87

UPHOLSTERY FABRIC: GRAIN/2288 FROM GABRIEL | PRICE CATEGORY 2

Composition: 80% post-consumer recycled polyester / 20% polyester
Durability: 100.000 Martindale
Pilling: 5
Light fastness: 5-7
Cleaning: wash or dry cleaning
Fire resistant: Yes



61247 62123 64251 66233 68258 60323

OEKO-TEX® CONFIDENCE IN TEXTILES STANDARD 100

10 year guarantee against wearing through

INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.

INTO
the Nordic Silence




POINT CUP

POINT CUP office booth is a sound-friendly 360-degree furniture solution that offers a comfortable space for presentations and video conferences.

TECHNICAL INFORMATION

SOCKETS	One electrical socket on the table + 3 sockets in the screen wall.
SCREEN	Screen wall is suitable for 20-42" screen. Screen wall does not include screen nor bracket for it.
ELECTRICITY CONNECTION	The length of the electric cord for the POINT CUP solution is 3 m.
MATERIAL DESCRIPTION	Office booth sofa modules with plywood frame, polyurethane foam and fabric upholstery. Table with structural paint top and powder-coated steel base. Base board painted MDF. Screen wall painted MDF and felt from the back.
OPTIONS	Tabletop with laminate.
MEASUREMENTS	W2450 x D2350 x H1420 mm TOP CUP table Ø900 / H720 mm




INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.

INTO
the Nordic Silence

All our materials comply with M1 emission classification.

UPHOLSTERY FABRIC FOR POINT CUP: MAIN LINE FLAX FROM CAMIRA | STANDARD PRICE, CATEGORY 1


Composition: 70% Virgin wool, 30% Flax
Durability: 50.000 Martindale
Lightfastness: 5
Crocking: 3/wet, 4/dry
Sustainability: Complies with EU ecolabel “The Flower”, Compostable
Cleaning: Vacuuming and dry cleaning
Fire resistant: Yes



MLF02 MLF14 MLF16 MLF19 MLF24 MLF67 MLF37

UPHOLSTERY FABRIC FOR POINT CUP: PYTON FROM DELFOS FR | CATEGORY 2

Synthetic leather
Composition: 77% PVC, 23% CO
Abrasion / Martindale: dry = 51.200 /cycles, wet = 12.800 /cycles
Lightfastness: 5
Crocking: 4-5
Breathable
Fire resistant: Yes / Flame retardant, IMO Certificate



0796 Negro 1112 Smoke 0793 Mocca 1168 Cashmere

Cleaning:
Because of its characteristics, clean and care the material frequently, with lukewarm water and a damp cloth, preferably of micro fibre. Soiling may be treated with a mild soap and proceed next to its drying by using a hairdryer or, failing that, a drymcloth. It should be avoided that areas that have been treated for cleaning remain wet



breathable and flame retardant quality | efficient material | long-life | easy-to-clean | aesthetic value

UPHOLSTERY FABRIC FOR POINT CUP: SYNERGY FROM CAMIRA | CATEGORY 2


Composition: 95% Virgin wool, 5% Polyamide
Durability: 100.000 Martindale
Pilling: 4
Lightfastness: 5
Cleaning: vacuuming and dry cleaning
Fire resistant: Yes



LDS08 LDS16 LDS17 LDS48 LDS56 LDS59 LDS87

UPHOLSTERY FABRIC FOR POINT CUP: GRAIN/2288 FROM GABRIEL | PRICE CATEGORY 2

Composition: 80% post-consumer recycled polyester / 20% polyester
Durability: 100.000 Martindale
Pilling: 5
Light fastness: 5-7
Cleaning: wash or dry cleaning
Fire resistant: Yes



61247 62123 64251 66233 68258 60323

OEKO-TEX® CONFIDENCE IN TEXTILES STANDARD 100

10 year guarantee against wearing through

INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.

INTO
the Nordic Silence

Ask for more colors: sales@intoconcept.com

COLOR OPTIONS FOR POINT CUP TABLE

STANDARD PRICE, CATEGORY 1

NCS S 0500-N
Structural

PRICE CATEGORY 2


White
laminate

STEEL TUBE BASE | STANDARD PRICE, CATEGORY 1

RAL 9016

FELT FOR POINT CUP SCREEN WALL: FULDA MENT 60 FROM FILZFABRIK | STANDARD PRICE, CATEGORY 1

- Composition: 40% Polyamid, 60% Polypropylen
- Static electrical propensity: Antistatic
- Classification for use: Commercial / heavy use
- Fire resistant: Yes



109 101 144 121 140 159

SCREEN WALL COLOR | STANDARD PRICE, CATEGORY 1

NCS S 0500-N
Smooth

BASEBOARD COLOR | STANDARD PRICE, CATEGORY 1

NCS S 0500-N
Structural

INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.


INTO
the Nordic Silence



TOP TABLES

TOP TABLES are visually slender yet structurally steady table solutions that enable ergonomic and flexible work. Table sizes go from small laptop tables up to bigger working desks.

TECHNICAL INFORMATION	Available either fixed leg or height-adjustable leg. Height is adjusted with a gas spring from a handle installed on the edge of the table top.
MATERIAL DESCRIPTION	MDF table top painted with structural paint. Base powder coated steel.
MIX AND MATCH	Choose the tabletop and leg that suits your needs.
OPTIONS	Table top with laminate.
TESTED	INTO TOP tables are tested and approved according with standard EN 15372:2016 which is European furniture standard testing strength, durability, and safety.



INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.


INTO
the Nordic Silence



TOP TABLES

TOP TABLES are visually slender yet structurally steady table solutions that enable ergonomic and flexible work. Table sizes go from small laptop tables up to bigger working desks.

TECHNICAL INFORMATION	Available either fixed leg or height-adjustable leg. Height is adjusted with a gas spring from a handle installed on the edge of the table top.
MATERIAL DESCRIPTION	MDF table top painted with structural paint. Base powder coated steel.
MIX AND MATCH	Choose the tabletop and leg that suits your needs.
OPTIONS	Table top with laminate.
TESTED	INTO TOP tables are tested and approved according with standard EN 15372:2016 which is European furniture standard testing strength, durability, and safety.




INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.

COLOR OPTIONS FOR TOP AND TOP LIFT TABLES


STANDARD PRICE, CATEGORY 1

Standard paint color options



NCS S 0500-N
Structural

PRICE CATEGORY 2




White
laminate



Black
laminate

POWDER COATED STEEL TUBE BASE | STANDARD PRICE, CATEGORY 1

Standard base paint options



RAL 9016



RAL 9005


INTO
the Nordic Silence



FOCUS

FOCUS is private workstation on wheels, and it provides both visual haven and true peace of mind while working. This acoustic desk is upholstered in felt that not only looks good but also creates an acoustically friendly environment.

TECHNICAL INFORMATION	Wheels included. Table light with switch. 2 x electrical socket. The electric cord length for the FOCUS solution is 3 m.
MATERIAL DESCRIPTION	Bent board frame. Felt upholstered inside and outside. Fixed table painted with structural paint.
MEASUREMENTS	W1530 x D1400 x H1570 mm




INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.

INTO
the Nordic Silence

All our materials comply with M1 emission classification.


FELT: FULDA MENT 60 FROM FILZFABRIK | STANDARD PRICE, CATEGORY 1

Composition: 40% Polyamid, 60% Polypropylen
Static electrical propensity: Antistatic
Classification for use: Commercial / heavy use
Fire resistant: Yes



109 101 144 121 140 159

COLOR OPTION FOR THE TABLE | STANDARD PRICE, CATEGORY 1



NCS S 0500-N
Structural

INTO
the Nordic Silence



ROLL IN

ROLL IN is a workstation with wheels that offers a handy haven for those who need to focus in private during their workday. This workstation with wheels includes fixed lighting, a built-in electrical socket as well as two bag hooks under the table.

TECHNICAL INFORMATION


Lockable wheels included.
2 x built-in electrical socket.
2 x bag hooks under the table.
Light with switch.
The electric cord length for the ROLL IN solution is 3 m.


MATERIAL DESCRIPTION

MDF frame with tabletop painted with white structural paint or optionally veneer frame with veneer tabletop.
Base powder-coated steel.
Acrylic window.

MEASUREMENTS

W1190 x D680 x H1510 mm






INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.

INTO
the Nordic Silence

All our materials comply with M1 emission classification.

SURFACE FINISHES FOR ROLL IN:

| STANDARD PRICE, CATEGORY 1



NCS S 0500-N
Smooth

PRICE CATEGORY 2



Oak veneer

INSIDE PANEL FABRIC: SOUL FROM GABRIEL | STANDARD PRICE, CATEGORY 1

Composition: 100% wool
Lightfastness: 5-7
Rubbing fastness: 4/wet, 4-5/dry
Sustainability: Complies with STANDARD 100 by OEKO-TEX
Meet Möbelfakta requirements
Cleaning: regular vacuum cleaning
Fire resistant: Yes (S 476 Part 7, class 1 ÖNORM B 3825-B1-3800-Q1 UK)




66104 67039 68131 64086 62059 61196 60182

OEKO-TEX® CONFIDENCE IN TEXTILES STANDARD 100

10 year guarantee against wearing through

TABLE TOP PAINT FOR ROLL IN:

STANDARD PRICE, CATEGORY 1



NCS S 0500-N
Structural


STANDARD PRICE, CATEGORY 2



Oak veneer

STEEL TUBE BASE | STANDARD PRICE, CATEGORY 1

Standard base paint options



RAL 9016 RAL 9005

INTO
the Nordic Silence



STORY WALL

STORY WALL is a multipurpose space divider on wheels. It absorbs sound waves creating pleasant sound environment, is easy to move around the premises, and adapts to customer's needs with its various add-on pieces.


TECHNICAL INFORMATION Includes wheels and adjustable support legs.

MATERIAL DESCRIPTION Plywood + chipboard frame filled with acoustical wool. Both sides upholstered with felt.

OPTIONS TO ADD


- TV bracket
- Corner piece
- Whiteboard
- Marker tray
- Basketball basket
- Dartboard
- Magazine holder
- Small shelf
- Big shelf
- Small coat hanger
- Big coat hanger

MEASUREMENTS W1190 x D600 x H2100 mm



FELT FOR STORY WALL: FULDA MENT 60 FROM FILZFABRIK | STANDARD PRICE, CATEGORY 1

Composition: 40% Polyamid, 60% Polypropylen
Static electrical propensity: Antistatic
Classification for use: Commercial / heavy use
Fire resistant: Yes




109 101 144 121 140 159

All our materials comply with M1 emission classification.

INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.

INTO
the Nordic Silence



CORNER PIECE FOR STORY WALL

Corner piece for the STORY WALL can be used to create corners and therefore, for example, rooms and nooks for teamwork and brainstorming.

TECHNICAL INFORMATION	Includes strong magnets for attaching to the STORY WALL.
MATERIAL DESCRIPTION	Chipboard frame. Both sides upholstered with felt.
MEASUREMENTS	W260 x D75 x H2000 mm


EXAMPLES OF HOW TO USE





FELT FOR STORY WALL CORNER PIECE: FULDA MENT 60 FROM FILZFABRIK | STANDARD PRICE, CATEGORY 1

Composition: 40% Polyamid, 60% Polypropylen
Static electrical propensity: Antistatic
Classification for use: Commercial / heavy use
Fire resistant: Yes



109 101 144 121 140 159

All our materials comply with M1 emission classification.

INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.

INTO
the Nordic Silence

KESKEN! PUUTTUU KUVAT

EXTRA HEIGHT PIECE FOR STORY WALL



Extra height piece allows STORY WALLS to be raised even higher to accommodate various spatial needs.

TECHNICAL INFORMATION

Easy installation by threading the extra height piece inbetween the two existing pieces.

MATERIAL DESCRIPTION

Plywood + chipboard frame filled with acoustical wool.
Both sides upholstered with felt.
Strong magnets on the sides.

MEASUREMENTS

W260 x D75 x H2000 mm


EXAMPLES OF HOW TO USE





FELT FOR STORY WALL CORNER PIECE: FULDA MENT 60 FROM FILZFABRIK | STANDARD PRICE, CATEGORY 1

Composition: 40% Polyamid, 60% Polypropylen
Static electrical propensity: Antistatic
Classification for use: Commercial / heavy use
Fire resistant: Yes




109 101 144 121 140 159

All our materials comply with M1 emission classification.

INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.

ACCESSORIES






Versatile the usage of the STORY WALL by adding fun and practical accessories. A shelf for books and pens, coat & hat hanger in various sizes, magazine holderto display documents and brochures, and whiteboards to share ideas and plans.

CABLE RAIL UNIT - Designed to order - minimum order 10 pieces





The cable rail unit hides cords of tv screens, chargers, and light fixtures. It is a 120 mm additional piece for STORY WALL, made to tidily tug away cords.

INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.

INTO
the Nordic Silence



TV BRACKET FOR STORY WALL

Turn your space divider into a stylish screen holder.
TV Bracket comes with a marker tray that has an extend cord holder.

TECHNICAL INFORMATION	Holds a screen of maximum "42.
MATERIAL DESCRIPTION	Steel plate painted white.

INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.

INTO
the Nordic Silence

WHITEBOARD FOR STORY WALL

Convert your STORY WALL into an inspiration board with whiteboards. The whiteboard is easy to attach to the STORY WALL with a magnet, and multiple whiteboards can be attached side by side. There is an option for 1-4 whiteboards as add-on pieces.

TECHNICAL INFORMATION	Attaches to the STORY WALL with a magnet.
MATERIAL DESCRIPTION	Painted steel plate painted white. Magnetic surface.
MEASUREMENTS	W1120 x H790 mm

INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.

INTO
the Nordic Silence

MARKER TRAY FOR STORY WALL



Make working more efficient with a handy Marker tray to place under the whiteboard. The Marker tray is easily attached to the STORY WALL with a magnet.

TECHNICAL INFORMATION	Attachable with a magnet.
MATERIAL DESCRIPTION	Steel plate painted white.
MEASUREMENTS	W1119 x D72 x H101 mm

INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.

INTO
the Nordic Silence

interstuhl



UPIS1 ACTIVATION STOOL

UPis1 activation stool is height-adjustable bar stool. It is a flexible seating solution that combines spontaneity, creativity, and sustainability.

MATERIAL DESCRIPTION	Polyamide base.
MEASUREMENTS	Ø 330 mm x 450 - 630 mm
OPTIONS	Option for additional seating cushion for extra comfortability.

COLOR OPTIONS

smart white | deep grey | ice blue | soft red | fresh yellow | red

FABRIC FOR UPIS1 CUSHION: ERA FROM CAMIRA

Width: 140 cm
Weight: 448 g/lfm
Abrasion test: >100.000
Pilling: 4-5
Light fastness: 5
Fastness to rubbing: 4

ER01 | ER12 | ER53 | ER06 | ER33

INTO Concept Ltd reserves a right to make changes to product portfolio as well as moderate, enhancing changes to the products.