




POD 1

POD 1 is perfect for small confidential meetings and as an adaptable workspace for one person. Its insulating structure offers excellent acoustic protection from disruptive sounds. The installation doesn't require changes to existing structures or walls.

TECHNICAL DETAILS

Technical information

STC value 45
POD handedness left or right
One electrical socket max. 9 A
Electrical socket position on the left, right or back wall
Electricity connection from the ceiling or floor
Glass wall includes the INTO stripe window taping
Automated electric sockets, ventilation with speed mode,
lights with electronic motion sensor and separate electronic control unit on the wall

Material description

MDF frame with water based paint
Painted MDF door and door panels
Door handle with brushed stainless steel
Laminated acoustic safety glass windows 0.394 in
Acoustic panels on the ceiling
Back wall and floor coated with carpet

Standard carpet:	Fletco Ex-dono quartet
Standard POD colors:	White smooth NCS S 0500-N Light grey smooth NCS S 6000-N Dark grey smooth NCS S 7500-N
Standard door color:	White NCS S 0500-N

Options

Door and door panels with American oak
Door lock
Tailored window taping

Measurements


W66.93 x D66.93 x H91.34 in
Door 3.54 x 8.66 in



Electric systems of INTO PODS are SGS certified for North-America market area.

SURFACE FINISHES FOR POD ROOMS

- Standard paint color options



NCS S 0500-N
Smooth



NCS S 6000-N
Smooth



NCS S 7500-N
Smooth

SURFACE FINISHES FOR DOOR & DOOR SIDE PANELS

CATEGORY 1



NCS S 0500-N
Smooth

CATEGORY 2



American oak

CARPETS FOR POD ROOMS: EX-DONO QUARTET FROM FLETCO

- Composition: Polyester non woven
- Static electrical propensity: Antistatic
- Impact sound reduction: 25 dB
- Classification for use: Commercial / heavy use
- Fire resistant: Yes





393300



393340



393350



Ask for more colors! contact@intoconcept.com