

POD 4

POD 4 meeting rooms are perfect for private or confidential meetings as well as adaptable work spaces. The acoustic protection in this meeting room is excellent due to its insulating structure. The installation doesn't require changes to existing structures or walls.

TECHNICAL DETAILS

Technical information STC value 45.

POD handedness left or right Two electrical sockets max. 9 A

98.43

Electrical socket position on the left, right or back wall

Electricity connection from the ceiling or floor Glass wall includes the INTO stripe window taping Automated electric sockets, ventilation with speed mode,

lights with electronic motion sensor and separate electronic control unit on the wall

Material description MDF frame with water based paint

Painted MDF door and door panels

Door handle with brushed stainless steel

Laminated acoustic safety glass windows 0.394 in

Acoustic panels on the ceiling

Back wall and floor coated with carpet

Standard carpet: Fletco Ex-dono quartet

Standard POD colors: White smooth NCS S 0500-N

Light grey smooth NCS S 6000-N Dark grey smooth NCS S 7500-N

Standard door color: White NCS S 0500-N

Options Door and door panels with American oak

Door lock

Tailored window taping

Measurements W133.86 x D98.43 x H91.34 in

Door 3.54 x 8.66 in




Electric systems of INTO PODS are SGS certified for North-America market area.



SURFACE FINISHES FOR POD ROOMS

- Standard paint color options



SURFACE FINISHES FOR DOOR & DOOR SIDE PANELS

CATEGORY 1



NCS S 0500-N Smooth

CATEGORY 2



American oak

CARPETS FOR POD ROOMS: EX-DONO QUARTET FROM FLETCO

- Composition: Polyester non woven
- Static electrical propensity: Antistatic
- Impact sound reduction: 25 dB
- Classification for use: Commercial / heavy use
- Fire resistant: Yes







393300 393340

393350

EN 14041:2004
17
2531-CPR-CXA10107





Ask for more colors! contact@intoconcept.com